

POWER D-SUB 11W1 SOLDER CUP-FEMALE

ROHS COMPLIANT

SPECIFICATIONS:

ELECTRICAL:
 INSULATOR RESISTANCE: 5,000 MegOHMS Min.
 DIELECTRIC WITHSTANDING: 1,000 VAC r. m. s.
 OPERATING TEMPERATURE: -55°C ~ +125°C
 CONTACT RESTANCE: 30 MILLIOHMS Max.
 POWER PINS: SEE PART No. BELOW
 SIGNAL PINS: 3AMPS

MECHANICAL:
 CONTACT INSERTION FORCE: 4.5kg Max
 CONTACT SEPARATOR FORCE: 0.3kg Min
MATERIALS:
 CONTACTS: BRASS
 INSULATOR: PBT UL94V-0 RATED,
 230°C PROCESS TEMP.
SHELL: STEEL


FINISH:
SHELL: NICKEL

Ordering Code:

PDB11W1	-F	-G0	-B	-20	-00
①	②	③	④	⑤	⑥

- ① Series
- ② Contact Type:
M:Male F:Female
- ③ Contact NO. :
G0: Gold flash G1: 3u" Gold
G2: 5u" Gold G3: 10u" Gold
G4: 15u" Gold G5: 30u" Gold
- ④ Insulation Color Code:
B:Black L:Blue
W:White
- ⑤ Power AMP:
10 = 10AMPS; 20 = 20AMPS;
30 = 30AMPS; 40 = 40AMPS;
- ⑥ Series no

NOTE:
 SIGNAL AND POWER CONTACTS
 COME PRE-LOADED INTO INSULATORS



Unless Otherwise specified tolerance

X:±0.35
 X.X:±0.25
 X.XX:±0.20
 X.XXX:±0.15


SCALE: 1:1 UNIT:
 IN (mm)

DRAWN: junfon H

CHECKED: YANG

12/5/3

DATE



ASA Electronic
 WWW.AsA-Elec.com

AsA Electronic Co.

Tel : (+98) 21 66 73 56 82 Mob : (+98) 912 03 161 02

TITLE:
 POWER D-SUB 11W1 SOLDER CUP-FEMALE

DRAWING NO: PDB11W1-FXXXXX00

PRODUCT NO: PDB11W1-FXXXXX00