



SPECIFICATION
 Current Rating:1A Max.
 Dielectric Withstanding Voltage:500V(AC) For 1 Minute
 Contact Resistance:30 Milliohms Max.
 Insulation Resistance:1000 Megaohms Min. At 500V DC
 Temperature Range:-55°C~+105°C
 RoHS Compliant

No.	Name	Q'ty	Material	Finish
1	Housing	2	PBT UL94V-0	Ivory
2	Contact	4	Brass	Gold Plated
3	Front Shell	1	Cold Rolled Steel	Nickel Plated
4	Back Shell	1	Cold Rolled Steel	Nickel Plated

ASA Electronic
 WWW.AsA-Elec.com
AsA Electronic Co.
 Tel : (+98) 21 66 73 56 82 Mob : (+98) 912 03 161 02

DRAWING No.		APPROVED BY		UNLESS OTHERWISE SPECIFIED TOLERANCES ARE .X ±0.30 .XX ±0.20 .XXX ±0.10 ANG. ±1°
Telegram: 09396994470		MEI		
		CHECKED BY	HZF	
		DRAWING BY	XYH	
SCALE	NONE	REV.	A2	UNIT mm

NO.	REV.	REVISIONS	CHK	DATE
△2	A2	Modify Data	HZF	05/12/2009
△1	A1	Modify Data	BECKY	06/07/2005
△0	A0	NEW RELEASE	RAN	