



SPECIFICATION

Current Rating: 1Amp
 Insulation Resistance: 1000MΩmin
 Contact Resistance: 20MΩmax
 Withstand Voltage: 500V AC/DC
 Contact Material: Brass
 Contact Plating: Au or Sn Over Ni
 Insulator Material: PA6T+30%GF UL 94V-0
 Operating Temperature: -40°C to +105°C

Ordering Code:

BHAR03 - X - X - X - X - X
 ① ② ③ ④ ⑤ ⑥

- ① Series No:
- ② No. of Contacts
10-100P
- ③ Contact Plating:
 G0: Gold flash S0: Selective
 G1: 3u" Gold S1: Selective 3u"
 G2: 5u" Gold S2: Selective 5u"
 G3: 10u" Gold S3: Selective 10u"
 G4: 15u" Gold S4: Selective 15u"
 G5: 30u" Gold S5: Selective 30u"
 SN: Tin
- ④ Color Insulator
 B: Black
 U: Blue
 W: White
- ⑤ Insulator Material
 A: PA6T
 B: LCP
 E: PA9T
- ⑥ Packing
 A: Tray
 B: Bag
 T: Tube
 U: Tube+CAP
 R: Tape&Reel
 W: Tape&Reel+CAP

AsA Electronic Co.
 WWW.AsA-Elec.com
 Tel: (+98) 21 66 73 56 82 Mob: (+98) 912 03 161 02

Unless Otherwise specified tolerance	
X. ±0.35	X. XX: ±0.20
X. X: ±0.25	X. XXX: ±0.15
SCALE: As Shown	UNIT: mm
DRAW YG ZHONG	DATE 01/05/2016
CHECK H.Z	DATE 01/05/2016

Telegram:09396994470	
TITLE: 1.27mm Box Header 90 ,H=5.4mm	
DRAWING NO:	BHAR03-XXXXXX
PRODUCT NO:	BHAR03-XXXXXX

REV	DESCRIPTION	DATE
1		
2		
3		
4		
5		

