

ELECTRICAL CHARACTERISTICS:


Dielectric withstanding Voltage: AC 1000V r.m.s.
Insulation Resistance: 500 Megohms Minimum at DC 500V
Contact Resistance: 25 Milliohms
Operating Temperature: -20°C~+85°C

Insulator: PBT, UL 94V-0 Rated
Shell: Cold Roller Steel

Ordering Code:

PDC1W1	-M	-G0	-B	-X	-00
(1)	(2)	(3)	(4)	(5)	(6)

- ① Series
- ② Contact Type:
M:Male F:Female
- ③ Contact NO. :
G0: Gold flash G1: 3u" Gold
G2: 5u" Gold G3: 10u" Gold
G4: 15u" Gold G5: 30u" Gold
- ④ Insulation Color Code:
B:Black L:Blue
W:White
- ⑤ Mounting Option:
A: Through-hole
B: 2.55" Threaded insert
C: 6.80" Threaded rear spacer
D: 10.3" Threaded rear spacer
PCB clip
E: 11.0" Threaded rear spacer
PCB clip
F: 11.9" Threaded rear spacer
PCB clip
- ⑥ Series

Unless Otherwise specified tolerance $X \pm 0.35$ $X.X \pm 0.25$ $X.XX \pm 0.20$ $X.XXX \pm 0.15$		 WWW.AsA-Elec.com AsA Electronic Co.	
SCALE: 1:1	UNIT: mm	Tel : (+98) 21 66 73 56 82 Mob : (+98) 912 03 161 02	
DRAWN: junfon H		TITLE: Coaxial D-SUB 1W1 MALE Solder Cup	
CHECKED: YANG		DRAWING NO: PDC1W1-MXXXX00	
 3rd ANGLE PROJECTION		PRODUCT NO: PDC1W1-MXXXX00	