

Coaxial D-SUB 27W2 FEMALE Solder Cup

ROHS COMPLIANT

ELECTRICAL CHARACTERISTICS:

Dielectric withstanding Voltage: AC 1000V r.m.s.
Insulation Resistance: 500 Megohms Minimum at DC 500V
Contact Resistance: 25 Milliohms
Operating Temperature: -20°C~+85°C

MATERIALS:


Insulator: PBT, UL 94V-0 Rated
Shell: Cold Roller Steel

Ordering Code:

PDC27W2 -F -G0 -B -X -00
① ② ③ ④ ⑤ ⑥

- ① Series
② Contact Type:
M:Male F:Female
③ Contact NO.:
G0: Gold flash G1: 3u" Gold
G2: 5u" Gold G3: 10u" Gold
G4: 15u" Gold G5: 30u" Gold
④ Insulation Color Code:
B:Black L:Blue
W:White
⑤ Mounting Option:
A: Through-hole
B: 2.55" Threaded insert
C: 6.80" Threaded rear spacer
D: 10.3" Threaded rear spacer
E: 11.0" Threaded rear spacer
F: 11.9" Threaded rear spacer
⑥ Series

Unless Otherwise specified tolerance		 WWW.ASA-Elec.com ASA Electronic Co. Tel : (+98) 21 66 73 56 82 Mob : (+98) 912 03 161 02	
X.±0.35 X.X:±0.25 X.XX:±0.20 X.XXX:±0.15	SCALE: 1:1	UNIT: mm	TITLE: Coaxial D-SUB 27W2 FEMALE Solder Cup
DRAWN: junfon H	DRAWING NO: PDC27W2-FXXXX00		
CHECKED: YANG	PRODUCT NO: PDC27W2-FXXXX00		



REV		Add option of plating		12/7/17	
		DESCRIPTION		DATE	
1	2	3	4	5	6