

SPECIFICATION



Current Rating:	1Amp
Insulation Resistance:	5000M ohms min
Contact Resistance:	20M ohms max
Dielectric Withstanding:	AC500V
Operating Temperature:	-65°C to +125°C
Contact Material:	Brass
Insulator Material:	PBT,UL 94V-0
	Standard:PBT,UL94V-0 Black

Ordering Code:

PHBS03 - X - X - D - X - X - X - X
 (1) (2) (3) (4) (5) (6) (7) (8)

① Series No:

②No.of Contacts
02 To 100

③ Contact Plating
G0: Gold flash
G1: 3u" Gold
G2: 5u" Gold
G3: 10u" Gold
G4: 15u" Gold
G5: 30u" Gold
SN: Tin

④ Connector Type
D: Dual

⑤ Pin Length:
 $A+B+H1/H2$

Please mark the desired length in the A/B

⑥ Insulator Material

B:PA6T
C:LCP
D:PA46

⑦ Packing
A:Tray
B:Bag
T:Tube

⑧ Plastic High
H1:1.0mm
H2:1.5mm

Unless Otherwise specified tolerance

X.	± 0.35
X.X	± 0.25
X.XX	± 0.20
X.XXX	± 0.15

SCALE: 2:1	UNIT: mm
------------	-------------

30	DRAWN: junfon H
----	-----------------

1	CHECKED: YANG
---	---------------


WWW.AsA-Elec.com
 AsA Electronic Co.

Tel : (+98) 21 66 73 56 82 Mob : (+98) 912 03 161 02

TITLE:	1.00mm Pin Header Dual Row Straight Type
--------	--

DRAWING NO:	PHBS03-XXDXXXX
-------------	----------------

PRODUCT NO:	PHBS03-XXDXXXX
-------------	----------------

A	B
1.80	1.8
Optional	

3rd ANGLE PROJECTION

Add option of plating

10-08-28

REV

DESCRIPTION

DATE _____



3rd ANGLE PROJECTION

PRODUCT NO:

PHBS03-XXDXXX

1

2

3

4

5

6

8