



RECOMMENDED P.C.BOARD HOLE LAYOUT

P.C.B LAYOUT TOLERANCE:±0.05mm

30.48	33.56	35.56	13
27.94	31.02	33.02	12
25.40	28.48	30.48	11
22.86	25.94	27.94	10
20.32	23.40	25.40	9
17.78	20.86	22.86	8
15.24	18.32	20.32	7
12.70	15.78	17.78	6
10.16	13.24	15.24	5
7.62	10.70	12.70	4
5.08	8.16	10.16	3
2.54	5.62	7.62	2
C	B	A	PIN

Specifications:

Rated Current	3A AC, DC (AWG #28)				角度	±3	设计	日期	
Rated Voltage	250V AC, DC				63 < L	±0.3	审核	日期	
Contact Resistance	20mΩ max				16 < L ≤ 63	±0.2	核准	日期	
Insulation Resistance	1000MΩ min				4 < L ≤ 16	±0.1	比例	1:1	视图
Withstanding Voltage	550V AC/minute				1 < L ≤ 4	±0.05	单位	MM	页码
Temperature Range	-55 C to +105 C	胶壳	PBT UL94V-0	黑	L ≤ 1	±0.05	编号	30-12-25-013	
Applicable wire Range	AWG #30 to #26	部件	材质	颜色	未详细说明之公差		版本		

名称	TJC8 针座
型号	TJC8-A



 WWW.AsA-Elec.com

 AsA Electronic Co.

 Tel : (+98) 21 66 73 56 82 Mob : (+98) 912 03 161 02