



50.80	48.26	20
25.40	22.86	10
22.86	20.32	9
20.32	17.78	8
17.78	15.24	7
15.24	12.70	6
12.70	10.16	5
10.16	7.62	4
7.62	5.08	3
5.08	2.54	2
B	A	PIN


  
 WWW.ASA-Elec.com
   
 AsA Electronic Co.
   
 Tel : (+98) 21 66 73 56 82 Mob : (+98) 912 03 161 02

Specifications:

Rated Current	3A AC, DC (AWG #26)			角度	±3	设计	日期
Rated Voltage	150V AC, DC			63 <math>\triangleleft L</math>	±0.3	审核	日期
Contact Resistance	20mΩ max			16 <math>\triangleleft L \trianglelefteq 63</math>	±0.2	核准	日期
Insulation Resistance	1000MΩ min			4 <math>\triangleleft L \trianglelefteq 16</math>	±0.1	比例	1:1
Withstanding Voltage	1000V AC/minute			1 <math>\triangleleft L \trianglelefteq 4</math>	±0.05	单位	MM
Temperature Range	-25 C to +85 C	胶壳	PA66	黑	L <math>\trianglelefteq 1</math>	±0.05	编号
Applicable wire Range	AWG #30 to #26	部件	材质	颜色	未详细说明之公差	版本	BY/A2019

名称	TJC8 带锁公壳
型号	TJC8-YSA